CUSTOMER SERVICE BULLETIN

Radio Shaek

Bulletin No. 45Ø2-4

Description Inventory Management

Model

Model II

Stock No.

26-4502 Version 1.1

Date

June 18, 1980

Page 1 of 2

400 Atrium—One Tandy Center, Fort Worth, Texas 76102

Problem

If a customer goes into the Review/Edit Inventory Items and changes the stock number, the vendor number is sometimes changed to either zero or 201. The problem can be corrected by re-editing the vendor number back to what it should be and making the changes listed below.

Solution

The problem is corrected by following the steps listed below.

Version 1.0

- 1. Backup the diskette(s) and make the changes on the Backup copy of the
- 2. In BASIC load the program by typing LOAD"RETINV".
- 3. Make the following corrections:

CHANGES (Retype the line or refer to the Edit section of the owners manual)

- Old Line: 2310 PUT1, I(I, 0): GOSUB1040: IFKF <> OTHENKF = 0: N1 = I: N2 = I(I, 0): $I(I,\emptyset)=-I(I,\emptyset):ND=ND+1:GOSUB314\emptyset:NI=NI-1$
- New Line: 2310 PUT1, $I(I,\emptyset)$: GOSUB1040: IFKF<>0THENKF=0:N1=I:N2=I(I,0): $I(I,\emptyset)=-I(I,\emptyset):VN=I(I,1):ND=ND+1:GOSUB314\emptyset:NI=NI-1$
- 4. Type SAVE"RETINV" to save the changes in the program.
- At TRSDOS Ready, make a backup copy of the corrected diskette.

CUSTOMER SERVICE BULLETIN

Inventory Management Bulletin # 4502-4 Subject ____

Page _____

2_ **Of** __2_

Version 1.1

- 1. Backup the diskette(s) and make the changes on the Backup copy of the program.
- 2. In BASIC load the program by typing LOAD"IMS/BAS".
- 3. Make the following corrections:

CHANGES (Retype the line or refer to the Edit section of the owners manual)

- Old Line: 234 PUT1,I(I,Ø):GOSUB184:IFKF<>ØTHENKF=Ø:N1=I:N2=I(I,Ø): $I(I,\emptyset)=-I(I,\emptyset):ND=ND+1:GOSUB292:NI=NI-1$
- New Line: 234 PUT1, $I(I,\emptyset)$: GOSUB184: IFKF<> \emptyset THENKF= \emptyset : N1=I:N2=I(I, \emptyset): $I(I,\emptyset)=-I(I,\emptyset):VN=I(I,1):ND=ND+1:GOSUB292:NI=NI-1$
- 4. Type SAVE"IMS/BAS" to save the changes in the program.
- 5. At TRSDOS Ready, make a backup copy of the corrected diskette.